

Make AI Great Again

CS230

Naveen Srivatsa nns@stanford.edu Stephanie Scott smscott@stanford.edu

Generating Tweets in 'Presidential' Style Using Recurrent Neural Networks

President Donald Trump's Twitter account has been noted for its distinctive writing style. We attempt to build a recurrent neural network that trains on 2,829 @realDonaldTrump tweets in order to generate new tweets in the style of the president. A neural network that trains on words rather than characters and consists of 4 bidirectional LSTM layers generates tweets that closely resemble @realDonaldTrump's tweets.The addition more layers or dropout regularization has some minimal impact on the quality of the output.

Data & Features

The dataset consists of 2,829 tweets issued by the @realDonaldTrump Twitter account between March 4, 2017 and May 31, 2018. Retweets are excluded. Replies by @realDonaldTrump are included. Tweets were extracted using the TwDocs tool. Some preprocessing was required: President Trump uses a significant number of ampersands that were extracted as "\&" and therefore were manually replaced with the proper character. Pre-processing and normalization required for training varied by model.


The Character Based Model uses a tokenizer that converts each character into an integer and is then normalized. Next, the base model applies one LSTM layer containing 256 LSTM units, applies dropout regularization, and applies a softmax activation layer. Adam optimizer is used, with learning rate of 0.001, beta1 of 0.9, and beta2 of 0.999.

The Word Based Model uses a tokenizer to turn each word into an integer corresponding to a token in a dictionary. Next, the model feeds embeddings into two sequential LSTM layers that contains 128 LSTM units each. The embedding and outputs of both LSTM layers are concatenated and fed into an attention layer that calculates the weighted average of inputs over time and outputs a context vector. Last, a dense layer applies a softmax activation. RMSprop is used with with learning rate of 0.004.

Results – Model Performance

Model	Description	Loss	Sample output
Character: Base	1-layer LSTM with	1.8479 (after	uic oi the resuic oi the resuic oi the
model	dropout, learning rate	96 epochs)	resuic oi the resuic oi the resuic oi
	= 0.001		the resuic oi the resui
Character: Base	1-layer LSTM with	2.0593 (after	people of the fake news the search
+ Faster learning	dropout, learning rate	19 epochs)	wery searri the people of the fake
	= 0.01		news the searet wery searri t
Character: Two-	2-layer LSTM with	1.5376 (after	and the fake news media is a grea
layer	dropout, learning rate	50 epochs)	honor to welcome the united state
	= 0.001		and the people of the world fo
Character: Base	1-layer bidirectional	1.9569 (after	the sireate niane on the uarl and seau
+ bidirectional	LSTM with dropout,	36 epochs)	rity oo the sases and secori big tee
	learning rate = 0.001		io the uasling onft to
Character: Two-	2-layer bidirectional	1.3889 (after	the fake news media is a great state
layer + bidirec-	LSTM, learning rate =	26 epochs)	of the fake news media is a disaster
tional	0.001		
Word: Base	4-layer, 128-cell	1.9735 (after	A thateres', my of ranto the w/ Yomi
model (on	Bidirectional LSTMs,	10 epochs)	resut dime the we the secuse, GRIO
characters)	learning rate = 0.004		
Word: Base	4-layer, 128-cell	0.2435 (after	general john kelly is doing a grea
model	Bidirectional LSTMs,	100 epochs)	job as chief of staff . all american
	learning rate = 0.004		strong on mexico on this our countr
			vote for against the next administra
			tion . if no support !
Word: Base	4-layer, 128-cell	0.2577 (after	steve bannon will be interviewed
model + dropout	Bidirectional LSTMs,	100 epochs)	by @ seanhannity at 9pme on 6
	learning rate = 0.004 ,		foxnews
	dropout = 0.2		
Word: Base	8-layer, 128-cell	0.2875 (after	michael wolff is a total loser who
model + dropout	Bidirectional LSTMs,	150 epochs)	made up stories in order to sell thi
+ 8 layer	learning rate = 0.004 ,		would go up classified information
	dropout = 0.2		spending!

Results - Loss under varying architectures and parameters for model with multiple LSTM layers



Discussion

Character vs Word Model - A multi-layer character model can reproduce words and phrases that resemble President Trump's tweets (e.g., "fake news"). Characterbased model is prone to spelling errors but captures capitalization. Word-based models are superior, as they can produce coherent sentences or tweets.

Learning Rate - Increasing the learning rate resulted in no meaningful decrease in the runtime of each epoch.

Dropout - Adding dropout to the 4-layer model improved performance and loss convergence slightly.

Bidirectional layers - Replacement of the feedforward layers with bidirectional layers in the two-layer characterbased models reduces the number of epochs required to achieve low levels of loss but increases the length of each epoch.

Exploding gradients - Character-based models with faster learning or bidirectional layers see evidence exploding gradient. Future versions of model should incorporate gradient norm clipping.

Overfitting - Some output tweets closely resemble input data (e.g., "Michael Wolff is a total loser who made up stories in order to sell"). Future versions of model should reduce levels of overfitting.

Future

We find that a neural network that trains on words rather than characters and consists of 4 bidirectional LSTM layers generates tweets that closely resemble

@realDonaldTrump's tweets. Future iterations of this model should begin with the word-based model and focus on reducing levels of overfitting.

https://github.com/sagar448/Keras-Recurrent-Neural-Network-Python
Pascanu, R., Mikolow, T., & Bengio, Y. (2013, February). On the difficulty of training re
International Conference on Machine Learning (pp. 1310-1318).
Woolf, M. (2017). Texteenrun, GitHub repository https://divibub.com/minimum.